

University of Stuttgart
Germany

Institute of Nuclear Technology
and Energy Systems




**Design, Construction
and Start-Up of a Test
Facility for
Experimental
Investigations of
Flow and Heat Transfer
with Supercritical CO₂**

W. Flaig, R. Mertz, J. Starflinger

Outline

- Motivation
- Objectives
- Test Facility
- Diffusion-Welded Heat Exchanger (DWHE)
- First Test Section
- Summary

Motivation




- High achievable heat transfer coefficients due to variable thermodynamic properties near the (pseudo-)critical point.
- Heat transfer applications for conventional and nuclear power plants.
- High cycle efficiency envisaged for high temperature applications.


Objectives

- Design and construction of a test facility for experiments with supercritical CO₂ for variable test sections.
- Basic investigations and fundamental research, e.g.
 - Heat transfer using supercritical CO₂ as working fluid.
 - Passive safety system for nuclear power plants.
 - Validation of DNS and Large-Eddy-Simulations.
- CO₂ technology development and testing.
- Data measurement and analysis.


Operating Range of the Test Facility



Piping and Instrumentation Diagram



CAD-Sketch of the Test Facility



Recent Pictures



- Construction, insulation and first improvements finished.
- Start-Up successful.
- Digital controlling implemented.
- First measurements are running.




Experimental Parameters

Parameter	Symbol	Value	Unit
Mass flow	\dot{m}	0.013 – 0.111	kg/s
Temperature	T	5.0 – 150.0	°C
Pressure	p	7.5 – 12.0	MPa
Inner Pipe Diameter	d_i	10.1	mm
Cooling Power	P_{cool}	20 - 50	kW
Electrical Power	P_{el}	130	kW
Volume Pressure Vessel	V_{PV}	0.072	m ³

Measurement Equipment


Parameter	Device	Range	Accuracy
Mass flow	Coriolis flow meter	0.013 – 0.130 kg/s	0.5 %
Temperature	Pt-100 resistance thermometer	-20 – 200 °C	0.15 K + 0.002 • [T]
Pressure	Piezoresistive pressure transmitter	0 – 30 MPa	0.15 %
Liquid level	Differential pressure transmitter	200 – 1000 mm	0.075 %

Application: Heat Removal at BWR




- System shall be retrofitted in current nuclear reactors, example shows BWR application.
- Compact heat exchanger necessary due to restriction of space inside containment.

Diffusion-Welded Heat Exchanger



- Relation: Surface to volume ratio A_H/V_{HE} is very high. Compact heat exchanger are necessary due to restriction of space inside containment.
- Low weight, low space requirements and less mass of structure material. Applicable for temperatures from -200 to 900 °C and pressure up to 60 MPa. Suitable for gas, liquids and 2-phase-mixtures.
- Higher heat transfer coefficients obtainable.

Diffusion-Welded Heat Exchanger




Milling/etching of channels

(Diffusion-)bonding of single plates


Combining to plate-packages

Welding of flanges




In house welding sample of a diffusion-bonded micro heat exchanger



Welding of the Heat Exchanger



Welding sample




- High quality weldseams achievable.
- Small deformation of channels.




1.4301
V2A-Stainless-Steel

First Test-Section: DWHE




- Analysis of heat transfer to supercritical CO₂.
- FEM/CFX-Simulations of flow and heat transfer, e.g. Comsol, Matlab.
 - Heat transfer capacity, heat transfer coefficients und pressure drop.
 - Favourable operating ranges.

First Test-Section: DWHE




**CAD-sketch of the first Test-Section:
DWHE**




Test section before welding

First Results: Start-Up of the facility




- Factor of influences on pressure and mass flow identified.

First Results: Start-Up of the facility



- Digital PID-Controller for high pressure and mass flow implemented.
- Stable steady-state operation achievable

First Results: Characteristic line of compressor



Summary

- Supercritical CO₂ shows favourable heat transfer properties for a wide temperature and pressure range.
- DWHE qualified in combination with supercritical CO₂ for efficient heat transfer.
- Research about thermo-hydraulic behaviour of CO₂ in DWHE.
- DWHE test section designed, manufactured and tested
- Test facility is operating.

Acknowledgment

This work was supported by a grant from the Ministry of Science, Research and the Arts of Baden-Württemberg (Az: 32-7533.-8-112/81) to Wolfgang Flaig.




Baden-Württemberg

MINISTERIUM FÜR WISSENSCHAFT, FORSCHUNG UND KUNST

DFG Deutsche
Forschungsgemeinschaft

The project leading to this application has received funding from the *Euratom research and training programme 2014-2018* under grant agreement No 662116.





University of Stuttgart
Institute of Nuclear Technology
and Energy Systems

Thank you!



Wolfgang Flaig

e-mail wolfgang.flraig@ike.uni-stuttgart.de

phone +49 (0) 711 685- 62454

fax +49 (0) 711 685- 62010

University of Stuttgart

Institute of Nuclear Technology and Energy Systems

Pfaffenwaldring 31

70569 Stuttgart

Application: Heat Removal at BWR

Parameter	Value	Unit
Predicted Heat Flux	60	MW
Heat flux density	100	kW/m ²
Mass flow	165	kg/s
Mass flow density	515	kg/m ² s
Hydraulic diameter	1.1	mm
Channels per plate	200	-
Basic area	650 x 650	mm
Surface area	600	m ²
Volume	1.2	m ³
Surface Density	500	m ² /m ³
Inlet temperature	67	°C
Inlet pressure	17.5	MPa

Literature Overview

CO₂ in power plants:

V. Dostal, M.J. Driscoll, P. Heijzlar: A supercritical Carbon Dioxide Cycle for Next generation Nuclear Reactors, MIT-ANP-TR-100 (2004).

S.A. Wright, P. S. Pickard, Bob Fuller.: "S-CO₂ Heated Un-Recuperated Brayton Cycle Development and Test Results" Sandia National Laboratories and Barber Nichols April 29,30 2009, RPI, New York

Heat Transfer with CO₂ as working fluid:

M. D. Carlson, A., Kruizenga, M. Anderson, M. Corradini.: Measurements of Heat Transfer and Pressure Drop Characteristics of Supercritical Carbon Dioxide Flowing in Zig-Zag Diffusion-Welded Heat Exchanger Channels, Supercritical CO₂ Power Cycle Symposium, Boulder, Colorado, 24.-25. May 2011.

P. C. Simões, J. Fernandes, J.P. Mota.: Dynamic model of a supercritical carbon dioxide heat exchanger, J. of Supercritical Fluids 35, S.167-173 (2005).

J.H. Song, H.Y. Kim, H. Kim, Y.Y. Bae.: Heat transfer characteristics of a supercritical fluid flow in a vertical pipe, J. of Supercritical Fluids 44, S.164–171 (2008).

Heat removal system:

J. Venker, D. von Lavante, M. Buck, D. Gitzel, J. Starflinger: Concept of a Passive Cooling System to Retrofit Existing Boiling Water Reactors, Proceedings of the 2013 International Congress on Advances in Nuclear Power Plants, ICAPP 2013, Jeju Island, Korea (2013).